








RUBBER WHEELS

Institutional Rubber Tyred Wheels

SUITABLE FOR LOADS UP TO **100KG** PER WHEEL

						
Wheel Diameter	Tyre Width	Boss Width	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
75	30	41	5/16 or 3/8"	BALL	80/45	IR3008*
100 100	32 32	41 41	5/16" or 3/8" 5/16"	BALL BALL	100/80 100/80	IR4007* IR4008
125 125	32 32	41 41	5/16" or 3/8" 5/16"	BALL BALL	100/80 100/80	IR5007* IR5008
150 150	32 32	41 39.6	5/16" 5/16"	BALL BALL	100/80 100/80	IR6008 IR6009*

Most attractive wheels with grey non marking rubber tyres complete with chrome centres (except *) sealed bearings and thread guards. Used in schools, hospitals, computer rooms.



IR4007



IR6008










MEDICAL



INDUSTRY

Anti Static Wheels

SUITABLE FOR LOADS UP TO **100KG** PER WHEEL

						
Wheel Diameter	Tyre Width	Boss Width	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
100	32	41	5/16"	BALL	100/80	AS4006
125	32	41	5/16"	BALL	100/80	AS5006

Anti static wheels have a leakage electrical resistance of less than 10,000 Ohm. The resistance can increase as a result of mechanical in uence. We also produce a large range of anti static polyurethane wheels. For technical advice please phone.



AS5006



MEDICAL



INDUSTRY