


FOR CLARITY IMAGES DO NOT SHOW ANY SAFETY GUARDING

The Eastall Pacman Coil Tilter is a small footprint upender for tilting coils of steel from a vertical to a horizontal bore position enabling safe loading to an Uncoiler machine. It is mechanically driven and can be stopped with the load held at any point in the turning process. This machine is robust, easily maintained and reliable with quality Australian-sourced componentry. Our 6 tonne model is standard and we can also manufacture to suit the tonnage required.

Safety aspects (on standard model)

- Start switch delay on turning the start switch there is a two second delay before commencement of operation.
- Audio visual warning turning the start switch immediately operates an orange flashing light and audible siren for the two seconds prior to commencement of operations and throughout the entire cycle of the machine.
- 'Deadman' start switch the start switch has to be continually held in place by the operator during the cycle of the machine. releasing the start switch will automatically cease operation of the machine.
- Separate operator console the manual controls are mounted away from the coil tilter for increased visibility.
- Fork tyne slots for safe and easy transportation and manoeuvring.



Weight: 1600 kg Working Load Limit (WLL): 6000 kg

OPTIONAL EXTRAS

- MESH GUARDING (if not installing your own)
- NARROW COIL STABILISERS
- CUSTOM PAINT COLOURS AVAILABLE



Eastall Precision Engineering

For a customised quote please enter details below

Name	YOUR DETAILS			
Name		Company name		
PH:		E-mail		
JOB DETAILS				
Max Coil Diameter	_{mm} Min (Coil Diameter	mm	
Max Coil width	mm N	In Coil width	mm	
Max Coil weight	kg			
GUARDING REQUIRED?		YES / NO		